

# IQL2 64 Thin Client

Entry-Level Dual Core Thin Client



Front View



Rear View

The ultra-compact and lightweight, IQL2 series is a flexible and entry-level thin client designed to support excellent multimedia capabilities.

Incorporating a superior build quality, the IQL2 series advanced features includes 4K dual displays, four USB3.0 ports and a powerful Intel® Apollo Lake Celeron™ N3350 Dual core System-on-a Chip (SoC), with a DDR3 memory controller.

An environmentally-friendly device, the IQL2 series efficient external power supply combined with a fan-less design, ensures a low power consumption and virtually silent operation.

Featuring an impressive three-year warranty backed by a comprehensive worldwide support network, the IQL2 series also includes a VESA mounting bracket and supports Fusion Universal Device Manager (UDM) Professional software which comes as standard.

The IQL2 series represents an unbeatable combination of affordability, quality, performance and service.

## Key Features

- Gio6 Linux
- Intel® Apollo Lake Celeron™ N3350 Dual core SoC for a rich multimedia and graphics experience
- Built-in Intel HD 500 Series Graphics
- RAM: DDR3L 1600 MHz through 2 x SO-DIMM slot
- Flash: Onboard 8GB / 32GB eMMC
- Built-in WiFi+Bluetooth (Optional)<sup>1</sup>
- Built-in Gigabit Ethernet networking with full duplex capability
- Dual digital display output (mDP and HDMI) with 4K resolution support.
- Fusion Universal Device Manager Professional included
- Kensington Lock
- VESA mounting bracket included



# IQL2 64 Thin Client

Entry-Level Dual Core Thin Client



## Technical specification

### Operating System

- Gio6 Linux

### Processor

- Intel® Apollo Lake Celeron™ N3350 upto 2.4 GHz Dual Core SoC
- 2MB shared L2 Cache
- Built-in Intel HD 500 Series Graphics Processor

### System Memory

- RAM : 2 GB upgradable upto 8 GB (with two SODIMM Slot)
- Flash: 8GB / 32 GB (Flash with higher capacities are available through M.2 slot)

### Display Support

- Dual digital display outputs with automatic setting of resolution and refresh rate
- Display Resolution (Max):  
mDP: 4096 x 2160 @60Hz ( 4K resolutions )  
HDMI: 3840 x 2160 @30Hz ( 4K resolutions )

### Rear Panel

- 1 x DC in connector
- 2 x Gigabit RJ45 Port
- 1 x HDMI Port
- 1 x mDP Port

### Front Panel

- Power Button
- 3 x USB 3.1 Gen1 Ports
- 1x USB 3.0 Type-C Port
- 1 x Combo Audio (Line out and MIC)

### Optional

- Intel Dual Band Wireless-AC 3165 Wi-Fi/Bluetooth 4.2 combo adapter <sup>1</sup>
- HDMI to DVI-D Cable
- HDMI to VGA Dongle

### External Power Adapter

- Worldwide auto-sensing 100-240 V AC
- DC output 19V / 3.42A

### Networking

- Auto-sensing 10/100/1000 Mbps Gigabit LAN
- Wake On LAN

### Operating Environment

- Operating Temperature: 0 to 40°C
- Storage Temperature: -20 to 60°C
- Humidity: 20% to 80% maximum, non-condensing

### Included Accessories

- VESA Dock (100x100 or 75x75 mounting holes)

### Physical Characteristics

- Dimension (W x D x H): 117x128x33 mm
- Weight : 0.45 kg

### Regulatory Compliance

#### Safety and EMC:

- CE, FCC and BIS

#### Energy and Environment:

- RoHS

#### Warranty

- Three years limited warranty

#### Software Support

- Citrix Receiver
- VMware Horizon Client
- RDP
- XfreeRDP
- Firefox (ESR)
- X11/XDMCP
- REXEC
- Spice
- VNC
- SSH
- Text Editor
- Data Card
- File Manager
- Google-Chrome

### Server OS Compatibility/Support

- Microsoft Windows Terminal Server Edition, Windows Server 2003/2008/2012
- Citrix XenApp / Citrix Presentation Server/ Citrix XenDesktop
- Protocol Support: TCP/IP, DHCP, FTP, HTTP, HTTPS

### Setup and Configuration

- Boot from local flash
  - Gio6 User interface language: US English
  - Keyboard Language support: English, Spanish, French and German
  - Scanners & Camera support
  - Smartcard support
  - ELO Touch screen support
  - USB input devices support
- #### Remote Management Tools

- Fusion Universal Device Manager (UDM) Professional
- Remote shadowing
- Reporting

### Note:

- <sup>1</sup> Available for selected countries only

### Part Numbers

Model No: IQL2 64 - F9R7 ---- 8 GB Flash / 2 GB RAM

Model No: IQL2 64 - F11R7 ----32GB Flash / 2 GB RAM

Model No: IQL2 64 - F11R8 ---- 32GB Flash / 4 GB RAM

## Contact Us

### Americas

Woodlands Business Centre , 32315 Tamina Road, Suite A, Magnolia, TX 77354, USA  
Tel: +1 877 242 7801

### Europe

Carrington Business Park, Manchester Road, Manchester, M31 4DD, UK  
Tel: +44 (0) 161 775 4755  
France Tel. : +33 616624515  
Germany Tel. : +49 (0) 8761 1093

### United Arab Emirates

1610, Tiffany Tower, Cluster 'W', Jumeirah Lake Towers, Dubai,  
UAE PO Box : 337111 Tel: +971 4 4508361

### India

4th Floor, Kimatrai Building, 77/79, Maharshi Karve Marg, Marine Lines(E), Mumbai - 400002, India  
Tel: +91 (0) 22 42203100

### Asia Pacific

6167, Jalan Bukit Merah, Tower 4; #06-12 (SR-46), Singapore 150167  
Tel: +65 6278 8180

E & OE: Specifications subject to change without notice. All trademarks are acknowledged and remain the property of their respective owners.

Document Version: A03